

# FUNKTION-ONE

## F88

The F88 comprises two Funktion One designed wide band 8" loudspeakers with a passively crossed over 2" coil slot tweeter delivering frequencies above 7kHz. Particular attention has been paid to the arrangement of the drive units to optimise coherency. The F88's 120° dispersion and 99dB sensitivity from 70Hz to 18kHz allows it to be used in numerous applications including under-balcony, theatre, bar/club, cinema surround and AV. The F88 will deliver full range sound in its own right but can be given more authority with the addition of Funktion-One bass enclosures.



### Features:

- Wide dispersion
- Wide bandwidth
- Funktion One designed 8" drivers
- Excellent clarity and intelligibility
- Rear mounting positions for alternative bracketry
- Funktion One Violet, Silver or Black finishes
- Optional mounting yoke/wall bracket
- Choice of curved, hex punched overall stainless steel grill or individual 8" grills for alternative aesthetics

Drivers	Sensitivity (1W at 1m)	Power (rms)	Nominal Impedance
2x8" 1 x HF Slot	99 dB	400W	6Ω

Frequency Response:

70Hz - 18kHz

Weight:

13 kg (28.6 lbs)

Nominal Dispersion:

120° x 40°

Connectors:

2 x NL4 Speakon

